

Technical data sheet



JX125-B-C PTFE MEMBRANE (Corrugated)

SPECIFICATIONS

| | | |
|--------------------------|-------------------|---|
| FILTERMATERIAL | | 100% POLYESTER |
| CONSTRUCTION | | BICO SPUN BOND + THERMAL BONDED PTFE MEMBRANE |
| PERMEABILITY | M3/M2/H AT 200 PA | 650 |
| WEIGHT | G/M2 | 130 |
| ELONGATION MD | % | 40 |
| ELONGATION CD | % | 45 |
| THICKNESS IN MM | MM | 0,42 |
| PORE SIZE | MICRON | |
| TENSTILE STRENGTH MD | N/5CM | 480 |
| TENSTILE STRENGTH CD | N/5CM | 300 |
| TEAR STRENGTH MD | N | 35 |
| TEAR STRENGTH CD | N | 30 |
| THERMAL SHRINKAGE MD | % | 3,5 |
| THERMAL SHRIANKAGE CD | % | 0,7 |
| MULLEN BURST | KG/CM2 | |
| TEMPERATURE RESISTANCE | C | 140 |
| HYDROPHOBIC RESISTANCE | | GOOD |
| ACID RESISTANCE | | GOOD |
| ALKALINE RESISTANCE | | GOOD |
| DUST RELEASE | | EXCELLENT |
| FILTER TEST | IFA/EN1822-3-2009 | M / E10 |
| EFFICIENCY OF 0,4 MICRON | % | |