

Product	Description / Treatment	Weight g/m ²	Air perm. m ³ /m ² /h	Filter-class
---------	-------------------------	-------------------------	---	--------------

80/20 Blend - Cellulose / Synthetic

JX140	80/20 (CELLULOSE/POLYESTER)	130	600	M
JX140FR	80/20+FLAME RETARDANT	135	600	M
JX135NANO	80/20+NANO	120	700	M / F9
JX135FR+NANO	80/20+FLAME RETARDANT+NANO	135	430	M / F9

Light weight - 100% Polyester

JX113-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	110	456	M
JX130B	100% BICO PET	130	1000-1100	
JX125-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	130	600-700	(E10)
JX125-B-C-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE, CORRUGATED	130	650	M / E10
JX130-B-NANO-9	100% BICO PET + NANO	140	1000	M / E10
JX130-B-C-NANO-9	100% BICO PET + NANO, CORRUGATED	170	730	M / F9
JX130-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	140	390-410	(E11)
JX130-B-C-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE, CORRUGATED	140	430	M / E11
JX131-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	140	300-350	E12
JX135-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	140	200-250	H13

Medium weight - 100% Polyester

JX180	100% PET	180	650-700	
JX180HO	100% PET+ OLEO/HYDROPHOBIC	180	600-700	
JX180FR	100% PET+FLAME RETARDANT	180	600-700	
JX180HO+FR	100% PET+OLEO/HYDROPHOBIC+FLAME RETARDANT	180	600-700	
JX180NANO	100% PET + NANO	165	795	M / E10
JX180ALU	100% PET+ANTISTATIC	180	600-700	
JX180ALU+HO	100% PET+ANTISTATIC+OLEO/HYDROPHOBIC	180	600-700	
JX180ALU+FR	100% PET+ANTISTATIC+FLAME RETARDANT	180	600-700	
JX180ALU+HO+FR	100% PET+ANTI+OLEO/HYDROPHOBIC+ FLAME RT	180	600-700	
JX180ALU-NANO	100% PET+ANTISTATIC+NANO	180	600	F9
JX180B	100% BICO PET	180	1000-1100	
JX180-B-NANO-9	100% BICO PET+NANO	180	680	M
JX179-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	180	500-600	(E10)
JX179-B-C-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE, CORRUGATED	180	550-600	(E10)
JX180-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	180	310	M / E11
JX180-B-C PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE, CORRUGATED	180	390	M / E11
JX181-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	180	250-300	(E12)
JX185-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	180	170-200	(H13)

Product	Description / Treatment	Weight g/m ²	Air perm. m ³ /m ² /h	Filter-class
---------	-------------------------	-------------------------	---	--------------

Heavy weight - 100% Polyester

JX240B	100% BICO PET	240	699	M
JX245-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	240	296	M / (E11)
JX260	100% PET	260	722	M
JX260HO	100% PET+OLEO/HYDROPHOBIC	260	410	M
JX260FR	100% PET+FLAME RETARDANT	260	400-450	(M)Fire cl.B2
JX260+HO+FR	100% PET+OLEO/HYDROPHOBIC+FLAME RETARDANT	260	400-450	(M)
JX260ALU	100% PET+ANTISTATIC	260	728	M
JX260ALU+HO	100% PET+ANTISTATIC+OLEO/HYDROPHOBIC	260	400-450	(M)
JX260ALU+FR	100% PET+ANTISTATIC+FLAME RETARDANT	260	400-450	(M)
JX260ALU+HO+FR	100% PET+ANTISTAT.+OLEO/HYDROPHOBIC+FLAM RT	260	400-450	(M)
JX260B	100% BICO PET	260	500-600	
JX260ALU-B	100% BICO PET+ANTISTATIC	260	500-600	
JX260-B-NANO-9	100% BICO PET+NANO	260	540	M
JX254-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	260	300-400	(E10)
JX255-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	260	288	M / E11
JX255-B-C-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE, CORRUGATED	270	330	M / E11
JX255-B-HO-PTFE MEMBRANE	100% BICO PET+ OLEO/HYDROP.(BOTH SIDES) +PTFE	270	200-250	(M)/(E11)
JX256-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	270	150-200	E12
JX265-B-PTFE MEMBRANE	100% BICO PET+PTFE MEMBRANE	260	140	M/H13/H14
JX260ALU-B-NANO-9	100% BICO PET+ANTISTATIC (BOTH SIDES) +NANO	270	680	M
JX254ALU-PTFE MEMBRANE	100% PET+ANTISTATIC+PTFE MEMBRANE	270	250-350	(E10)
JX255ALU-PTFE MEMBRANE	100% PET+ANTISTATIC+PTFE MEMBRANE	270	200	M / E11
JX255ALU-C-PTFE MEMBRANE	100% PET+ANTISTATIC + PTFE MEM., CORRUGATED	270	200-230	(E11)
JX256ALU-PTFE MEMBRANE	100% PET+ANTISTATIC+PTFE MEMBRANE	270	150-200	(E12)
JX265ALU-PTFE MEMBRANE	100% PET+ANTISTATIC+PTFE MEMBRANE	270	100-120	H13
JX255CB-B-PTFE MEMBRANE	100% BICO PET+CARBON IMPREGNATION+PTFE MEM.	270	200-300	E12

Additional services

OLEO/HYDROPHOBIC treatment of your material.
FLAME RETARDANT treatment of your material.
ALUMINUM COATING of your material.
NANO COATING of your material. (Electro spinning)
PTFE LAMINATION on your material. (Different membrane options)
CORRUGATION of your material.
SLITTING of your material.