

| Product | Description / Treatment | Weight g/m ² | Air perm. m ³ /m ² /h | Filter-class |
|---------|-------------------------|-------------------------|---|--------------|
|---------|-------------------------|-------------------------|---|--------------|

80/20 Blend - Cellulose / Synthetic

| | | | | |
|---------------------|--|-----|------|-----------|
| JX140 | 80/20 (CELLULOSE/POLYESTER) | 115 | 1150 | M |
| JX140FR | 80/20 + FLAME RETARDANT | 135 | 500 | M |
| JX135NANO | 80/20 + NANO | 120 | 430 | M / F9 |
| JX135FR-NANO | 80/20 + FLAME RETARDANT + NANO | 130 | 500 | M / F9 |
| JX136FR-NANO | 80/20 + FLAME RETARDANT + NANO (90% on 0,3 micron) | 122 | 420 | M |
| JX143-PTFE MEMBRANE | 80/20 (CELLULOSE/POLYESTER) + PTFE MEMBRANE | 125 | 300 | (M) / E10 |

Light weight - 100% Polyester

| | | | | |
|-------------------------|---|-----|------|-------------|
| JX130B | 100% BICO PET | 130 | 1800 | |
| JX130-B-C | 100% BICO PET, CORRUGATED | 130 | 2000 | |
| JX124-B-ECOWEB | 100% BICO PET + LAMINATED ECOWEB | 130 | 700 | (M) / F9 |
| JX124-B-C-ECOWEB | 100% BICO PET + LAMINATED ECOWEB, CORRUGATED | 130 | 750 | M / F9 |
| JX125-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 130 | 550 | (M) / (E10) |
| JX125-B-C-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE, CORRUGATED | 130 | 600 | M / E10 |
| JX130-B-NANO-9 | 100% BICO PET + NANO | 130 | 1000 | M / F9 |
| JX130-B-C-NANO-9 | 100% BICO PET + NANO, CORRUGATED | 130 | 1200 | M / F9 |
| JX130-B-NANO-FR | 100% BICO PET + NANO + FLAME RETARDANT | 130 | 1000 | (M) / (F9) |
| JX130-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 130 | 400 | (M) / (E11) |
| JX130-B-C-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE, CORRUGATED | 130 | 430 | M / E11 |
| JX131-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 130 | 180 | M / E12 |
| JX135-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 130 | 175 | M / H13 |
| JX130ALU-B-NANO-9 | 100% BICO PET + ANTISTATIC + NANO | 130 | 1000 | (M) / (F9) |
| JX130ALU-B-C-NANO-9 | 100% BICO PET + ANTISTATIC + NANO, CORRUGATED | 130 | 1200 | (M) / (F9) |

Medium weight - 100% Polyester

| | | | | |
|--------------------------|--|-----|------|-------------|
| JX180 | 100% PET | 170 | 1080 | |
| JX180HO | 100% PET + OLEO/HYDROPHOBIC | 170 | 1080 | |
| JX180FR | 100% PET + FLAME RETARDANT | 170 | 1080 | |
| JX180HO-FR | 100% PET + OLEO/HYDROPHOBIC +FLAME RETARDANT | 170 | 1080 | |
| JX180ALU | 100% PET + ANTISTATIC | 170 | 1080 | |
| JX180ALU-HO | 100% PET + ANTISTATIC + OLEO/HYDROPHOBIC | 170 | 1080 | |
| JX180ALU-FR | 100% PET + ANTISTATIC + FLAME RETARDANT | 170 | 1080 | |
| JX180ALU-HO-FR | 100% PET + ANTI + OLEO/HYDROPHOBIC + FLAME RT. | 170 | 1080 | |
| JX180B | 100% BICO PET | 170 | 1440 | |
| JX180-B-C | 100% BICO PET, CORRUGATED | 170 | 1640 | |
| JX180-B-NANO-9 | 100% BICO PET + NANO | 170 | 900 | M / F9 |
| JX180-B-C-NANO-9 | 100% BICO PET + NANO, CORRUGATED | 170 | 1100 | (M) / (F9) |
| JX178-B-ECOWEB | 100% BICO PET + LAMINATED ECOWEB | 170 | 500 | M / (F9) |
| JX178-B-C-ECOWEB | 100% BICO PET + LAMINATED ECOWEB, CORRUGATED | 170 | 600 | (M) / (F9) |
| JX179-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 170 | 400 | (M) / (E10) |
| JX179-B-C-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE, CORRUGATED | 170 | 500 | M / (E10) |
| JX180-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 170 | 350 | M / (E11) |
| JX180-B-C PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE, CORRUGATED | 170 | 400 | M / E11 |
| JX181-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 170 | 170 | (M) / (E12) |
| JX185-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 170 | 150 | (M) / (H13) |
| JX180ALU-B-NANO-9 | 100% BICO PET + ANTISTATIC + NANO | 170 | 900 | (M) / (F9) |
| JX180ALU-B-C-NANO-9 | 100% BICO PET + ANTISTATIC + NANO, CORRUGATED | 170 | 1100 | (M) / (F9) |
| JX180ALU-B-PTFE MEMBRANE | 100% BICO PET + ANTISTATIC + PTFE MEMBRANE | 180 | 300 | (M) / (E11) |
| JX180ALU-B-C-PTFE MEM. | 100% BICO PET+ANTISTAT.+PTFE MEM., CORRUGATED | 180 | 350 | (M) / (E11) |

| Product | Description / Treatment | Weight g/m ² | Air perm. m ³ /m ² /h | Filter-class |
|--------------------------------------|---|-------------------------|---|--------------|
| Heavy weight - 100% Polyester | | | | |
| JX260 | 100% PET | 260 | 470 | M |
| JX260HO | 100% PET + OLEO/HYDROPHOBIC | 260 | 470 | M |
| JX260FR | 100% PET + FLAME RETARDANT | 260 | 470 | (M) / B2 |
| JX260-HO-FR | 100% PET + OLEO/HYDROPHOBIC + FLAME RETAR- | 260 | 470 | (M) |
| JX260ALU | 100% PET + ANTISTATIC | 260 | 470 | M |
| JX260ALU-HO | 100% PET + ANTISTATIC + OLEO/HYDROPHOBIC | 260 | 470 | M |
| JX260ALU-FR | 100% PET + ANTISTATIC + FLAME RETARDANT | 260 | 470 | (M) |
| JX260ALU-HO-FR | 100% PET+ANTISTAT.+OLEO/HYDROPHOBIC+FLAM RT. | 260 | 470 | (M) |
| JX260B | 100% BICO PET | 240 | 1080 | |
| JX260-B-C | 100% BICO PET, CORRUGATED | 240 | 1400 | |
| JX260-B-HO | 100% BICO PET + OLEO/HYDROPHOBIC | 240 | 1080 | |
| JX260-B-C-HO | 100% BICO PET + OLEO/HYDROPHOBIC, CORRUGATED | 240 | 1400 | |
| JX260ALU-B | 100% BICO PET + ANTISTATIC | 240 | 1080 | |
| JX260ALU-B-C | 100% BICO PET + ANTISTATIC, CORRUGATED | 240 | 1400 | |
| JX260ALU-B-HO | 100% BICO PET + ANTISTATIC + OLEO/HYDROPHOBIC | 240 | 1080 | |
| JX240-B-FR | 100% BICO PET + FLAME RETARDANT | 240 | 1080 | K1 / F1 |
| JX240ALU-B-FR | 100% BICO PET + FLAME RETARDANT | 240 | 1080 | K1 / F1 |
| JX243-B-ECOWEB | 100% BICO PET + LAMINATED ECOWEB | 240 | 450 | (M) / F9 |
| JX243-B-C-ECOWEB | 100% BICO PET + LAMINATED ECOWEB, CORRUGATED | 240 | 550 | M / (F9) |
| JX260-B-NANO-9 | 100% BICO PET + NANO | 240 | 800 | M / F9 |
| JX260-B-C-NANO-9 | 100% BICO PET + NANO, CORRUGATED | 240 | 1000 | (M) / (F9) |
| JX254-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 240 | 380 | M / E10 |
| JX255-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 240 | 288 | M / E11 |
| JX255-B-C-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE, CORRUGATED | 240 | 370 | M / E11 |
| JX255-B-HO-PTFE MEMBRANE | 100% BICO PET+OLEO/HYDROPHOBIC+PTFE- | 240 | 288 | (M) / (E11) |
| JX256-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 240 | 160 | (M) / E12 |
| JX265-B-PTFE MEMBRANE | 100% BICO PET + PTFE MEMBRANE | 240 | 130 | M/H13/H14 |
| JX260ALU-B-NANO-9 | 100% BICO PET + ANTISTATIC + NANO | 240 | 800 | M / (F9) |
| JX260ALU-B-C-NANO-9 | 100% BICO PET + ANTISTATIC + NANO, CORRUGATED | 240 | 1000 | (M) / (F9) |
| JX254ALU-B-PTFE MEMBRANE | 100% BICO PET + ANTISTATIC + PTFE MEMBRANE | 260 | 290 | M / E10 |
| JX255ALU-B-PTFE MEMBRANE | 100% BICO PET + ANTISTATIC + PTFE MEMBRANE | 260 | 230 | M / E11 |
| JX255ALU-B-C-PTFE MEMBRANE | 100% BICO PET+ANTISTATIC+PTFE MEM.,CORRUGA- | 260 | 280 | (M) / (E11) |
| JX256ALU-B-PTFE MEMBRANE | 100% BICO PET + ANTISTATIC + PTFE MEMBRANE | 260 | 130 | (M) / E12 |
| JX265ALU-B-PTFE MEMBRANE | 100% BICO PET + ANTISTATIC + PTFE MEMBRANE | 260 | 110 | (M) / H13 |
| JX255CB-B-PTFE MEMBRANE | 100% BICO PET+CARBON IMPREGNATION+PTFE MEM. | 260 | 260 | (M) / E11 |

Additional services

| |
|---|
| OLEO/HYDROPHOBIC treatment of your material |
| FLAME RETARDANT treatment of your material (F1 / K1, B2) |
| ALUMINUM COATING of your material |
| NANO COATING of your material (Electro spinning) (F9) |
| PTFE LAMINATION on your material (E10, E11, E12, H13) |
| GLUE LAMINATION of your material (spunbond / meltblown, spunbond / ptf / glass-fiber, spunbond / ptf / meltblown) |
| CORRUGATION of your material |
| SLITTING of your material (50 mm-2400 mm) |
| PLEATING of your material (Width: 2100 mm / Depth: 15-50 mm) |